

MPT earthtone

High Build Acrylic Finish

Description:

MPT earthtone High Build Acrylic Finish is formulated on an adhesion promoted pure acrylic latex that imparts excellent adhesion, water and alkali resistance and exceptional weather resistance. The low sheen finish will promote good soil resistance and a finish that is easy to clean. The high build properties of this coating enhances application on difficult to apply substrates and produces a very tough finish. A dry film thickness of 80 microns per coat can be achieved.

Features and Benefits:

- Excellent adhesion and build over MPT earthtone Limebuster, MPT earthtone High Build Acrylic Finish and primed surfaces.
- Quick dry.
- High water and alkali resistance.
- Excellent weather resistance and low dirt pick-up.

Limitations:

- Do not apply when ambient temperature is below 10°C. or surface temperature is above 45°C.
- Apply as supplied – do not thin.

Technical Data:

Resin Type:	Adhesion Promoted Pure Acrylic polymer
Pigmentation:	Titanium dioxide and inert extenders
Solvents:	Water
Colour:	White, Deep Base and Ultra Deep Base
Gloss Level:	Low sheen
Density:	1.34 Kgs/ Litre
Dry-Time:	30 mins Touch, 4 hour between overcoat
Coverage:	4 – 6 M ² per litre
No. of coats:	Two
Packaging sizes:	10 Litre
Flash Point:	None
Thinner:	Water

Technical Data Sheet
Product No: MPTAW/10L



Surface Preparation:

Remove all unsound paint, surface grease and oil, dirt etc.
Treat mould affected areas with APCO Biowash Moss & Mould Remover.

Application:

For metal or metal reinforced concrete structures use a specified primer or A2000 High Build Sealer.
Apply one to two coats of MPT earthtone High Build Acrylic Finish to dry film thickness of 80 microns per coat.

For Best Results:

- 1) Ensure correct dry film thickness is achieved.
- 2) Allow at least 4 hours before over-coating.
- 3) Do not apply in direct sunshine.

Health and Safety: (Please refer to Material Safety Data Sheet before using)

MPT earthtone High Build Acrylic Finish is essentially non-flammable and non-hazardous.

KEEP OUT OF REACH OF CHILDREN



0800 BUY APCO
Ph. 09) 2733 041
Fax. 09) 2733 045

PO Box 58849
Botany
Manukau 2163