

MPT earthtone Limebuster

Description:

MPT earthtone Limebuster is a 100% acrylic penetrating sealer for unpainted, concrete and cementitious and fibre-cement plaster surfaces. It promotes adhesion of high build acrylic membrane coatings and helps to prevent the onset of efflorescence.

Features and Benefits:

- Excellent penetration and adhesion to concrete and cement surfaces.
- Strengthens friable cement surface.
- Helps to prevent the onset of efflorescence formation.
- Provides a base for MPT Earthtone finish coats.

Limitations:

- Do not apply when ambient temperature is below 10°C or surface temperature above 40°C.
- Do not overcoat when concrete is saturated.

Technical Data:

Resin Type:	100% Acrylic Emulsion
Pigmentation:	Titanium Dioxide
Solvents:	Water
Colour:	Translucent white
Density:	1.05 Kgs/ Litre
Dry-Time:	30 mins Touch, 2 hour sand and overcoat
Coverage:	6m ² per litre
No. of coats:	One full coat
Packaging sizes:	10 Litre
Flash Point:	None
Thinner:	Water
VOC:	71 g/L

Technical Data Sheet:
Product No: MPTLB/10L



Surface Preparation:

All surfaces must be clean, free from dust, oil, grease and other surface contamination.
For Mineral Plaster: Allow the plaster to set (carbonation) before painting.
For Concrete/Masonry: Allow a minimum of 28 days before painting.
Remove any trace of release agents from concrete/tilt slabs.

Application:

Apply one liberal coat, by brush, roller or airless spray at the recommended coverage rate, to a damp surface. To keep brushes and rollers working freely, rinse occasionally with clean water.

For Best Results:

- 1) Dampen/wet plaster surfaces.
- 2) Do not apply Limebuster in direct sunlight.
- 3) Ensure concrete, plaster & other alkaline surfaces have had the appropriate time to set/cure.

Health and Safety: (Please refer to Material Safety Data Sheet before using)

MPT earthtone Limebuster is essentially non-flammable and non-hazardous.

KEEP OUT OF REACH OF CHILDREN



0800 BUY APCO
Ph. 09) 2733 041
Fax. 09) 2733 045

PO Box 58849
Botany
Manukau 2163

V 3 -03.14