

Skimcoat

Description

Skimcoat is a cement based, all-purpose skimming render designed specifically as a levelling coat and a preparation coat for subsequent finishing coats.

Skimcoat contains only natural minerals and additives.

Skimcoat is designed primarily for use as a levelling and preparation coat during the application of these MPT Exterior Cladding Systems: AACclad, Fibreclad, Liteclad, Meshclad and Stoneclad.

Features and Benefits

- Easy application and handling.
- Easy to use on vertical and overhead applications.
- Excellent abrasion resistance.
- Excellent weather and solvent resistance.
- Excellent adhesion to MPT Bondcoat, MPT Skimcoat, MPT Litecoat and a variety of surfaces including fibre-cement and masonry.
- Levels surface imperfections for subsequent texture coats.
- Skimcoat does not decompose into hazardous by-products.

Limitations and Precautions

- Do not add anything other than clean water.
- Do not add additional water to Skimcoat later than two hours after original mixing.
- Apply only when the temperature is between 5° and 30°.
- Do not apply if a sudden temperature drop is likely during drying/cure time.
- Do not apply in hot, dry, windy conditions.
- Plaster must be protected from rain or water in the first 24 hours.

Technical Data	
----------------	--

Bag Size	20kg
Dry Time	24 hours Cool temperatures, high film thickness or high humidity may require longer drying times.
Theoretical Coverage	10 m ² per 20kg bag
No. of coats	1 coat
Flash Point	None
Thinner/Clean up	Water. Wash equipment and spills immediately with water. Ensure washing water does not enter waterways.
Theoretical VOC	1 g/kg

Surface Preparation

The surface must be dry. Remove all dirt, dust, grease, loose particles, mould or any other form of contamination from the surface. Any release agents must be completely removed.

Surfaces with defects, uneven areas or voids do not require special preparation.

Application

Stir the contents thoroughly before and during use.

Apply by commercial plastering machines or manual application (drill mixer only).

Skimcoat can be applied at a minimum thickness of 1mm and at a maximum thickness of 5mm.

For Best Results

- Do not apply in direct sunlight.
- Check the finished plaster system annually for cleanliness and integrity of the applied finish coatings.

Storage Store in a dry place on dunnage or a pallet, out of direct sunlight and away from moisture for up to 6 months.

Health and Safety (Please refer to the Material Safety Data Sheet before using)

MPT Skimcoat is non-flammable, non-hazardous, non-combustible & non-explosive.

KEEP OUT OF REACH OF CHILDREN

Product Number

MPT350

V 1 - 11.15

Please ensure you are referring to the current Datasheet.

Although the information and recommendations in this document are presented in good faith and believed to be correct, APCO Coatings (NZ) Ltd makes no representation as to the completeness and accuracy thereof. In no event will APCO Coatings (NZ) Ltd be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No representations or warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the information or Technical Datasheet refers. Users of this information should rely on their own professional judgment as to the suitability of this product for a specific purpose.