



## MPT earthtone High Build Primer

### Description:

MPT earthtone High Build Primer is based on an acrylic copolymer. It is a tough, high build coating that has excellent resistance to water and alkali. Its low sheen surface provides the ideal key for Earthtone High Build Acrylic Finish. Its high build helps smooth the finish of blocks and can be applied up to a dry film thickness of 80 microns per coat.

### Features and Benefits:

- Excellent adhesion.
- Excellent film build over rough concrete block.
- High water and alkali resistance.
- Quick dry.

### Limitations:

Do not apply when ambient temperature is below 10°C or surface temperature is above 45°C.

Do not thin - Apply as supplied

### Technical Data:

<b>Resin Type:</b>	Acrylic Emulsion
<b>Pigmentation:</b>	Titanium dioxide and inert extenders
<b>Solvents:</b>	Water
<b>Colour:</b>	White
<b>Gloss Level:</b>	N/A
<b>Density:</b>	1.42 Kgs/ Litre
<b>Dry-Time:</b>	30 mins Touch dry, 4 hours between overcoat Cooler temperatures, higher film thickness or high humidity will require longer drying times.
<b>Coverage:</b>	6 - 8m <sup>2</sup> per litre
<b>No. of coats:</b>	Two
<b>Packaging sizes:</b>	4 and 10 litre
<b>Flash Point:</b>	None
<b>Thinner:</b>	Water

### **Surface Preparation:**

Remove all dirt, unsound paint, surface grease, oil etc. Treat mould affected areas with APCO Biowash Moss & Mould Remover.

### **Application:**

Earthtone High Build Primer requires no undercoat or primerr except on galvanised iron and other metal surfaces. In areas with high levels of sunlight, Earthtone High Build Finish should always be used as a final topcoat. Apply a minimum of two coats or Earthtone High Build Primer by brush, roller or airless spray, a third coat may be necessary on some porous surfaces to ensure correct dry film thickness has been achieved. To keep brushes and rollers free, rinse regularly in clean water.

### **For Best Results:**

- 1) Ensure the correct dry film thickness is achieved.
- 2) Allow at least 4 hours before over-coating.
- 3) Do not apply in direct sunshine.

**Health and Safety:** (Please refer to Material Safety Data Sheet before using)

**MPT Earthtone High Build Primer** is essentially non-flammable and non-hazardous.

**KEEP OUT OF REACH OF CHILDREN**



0800 BUY APCO  
Ph. 09) 2733 041  
Fax. 09) 2733 045

PO Box 58849  
Botany  
Manukau 2163

**V 1**  
**5/14**

Although the information and recommendations set down here in this document are presented in good faith and believed to be correct, APCO Coatings NZ Ltd makes no representation as to the completeness and accuracy thereof. In no event will APCO Coatings NZ Ltd be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No representations or warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the information or Technical Data Sheet refers